

# ATH W®64 P Plus

## Product Images

---



## Description

---

- **Pneumatic shaft:** 40 mm clamping shaft for quick and secure wheel clamping
- **Sonar technology:** Non-contact rim width detection
- **Automatic positioning:** Automatically positions the wheel for weight attachment
- **Extended clamping shaft:** Additional clamping shaft for use with other clamping devices
- **Laser indicator:** Enables precise placement of the clamping weights at the 6 o'clock position
- **Static/Dynamic program:** Enables optimal balancing at different speeds
- **Alu balancing programs:** Special programs for aluminum rims to improve balancing quality
- **Split rear spoke weight positioning:** Enables precise weight distribution behind the spokes
- **Optimization program:** Program for fine-tuning and optimizing the balancing process
- **Optional motorcycle function:** Additional function for balancing motorcycle wheels
- **including wheel jack** ATH RRH1107

## Additional Information

---

Center hole diameter rim	45 – 130 mm
Measuring time car   truck	8 s
Measurement tolerance	+/- 1g
Measuring speed	200 U/min
Rim width	1,5" – 20"
Rim diameter	10" – 24"
Max. wheel diameter	900 mm
Wheel weight max.	65 kg
Compressed air connection	8 bar
Monitor	22" LED
Driving power	0,20 kW
Power supply voltage	230V / C16A

