

ATH Supreme Lift 2.40 HB

Product Images



- **Modern design – pioneering technology – impressive appearance**
- Electromechanical 2-post lift with space-saving “triangular columns” and spindle drive
- Two independent columns are controlled wirelessly via industrial Radio without any cross-connection
- Extremely durable and can be set up flexibly in width
- **ATH Supreme concept**
 - 1) ATH-HeartBeat PLC-controlled synchronization of two independent columns
 - 2) One electric motor, control unit and energy set per column
 - 3) Synchronization control with patented, double distance measurement for maximum safety
 - 4) Service-friendly changing of the support nuts possible when the column is stationary
- **ATH Supreme-Safety-System**
 - 1) Low-wear plastic support nut
 - 2) Solid safety nut
 - 3) Wear indicator
 - 4) Mechanical nut breakage safety unit
 - 5) MicroAnts monitoring of all electronic components
- Can be operated from any column
- Power set (230V / compressed air / USB) on both columns
- Multifunctional mounting via 3-part support arms and double telescopic support plates (optionally with double articulated arm at the rear)t
- Qualitative enhancement of every workshop with high-quality and attractive design, by covering all components

Additional Information

Color	Anthrazitgrau
Rated load capacity	4.000 kg
Lifting height max.	2.000 mm
Drive-through width	2.310 – 2.500 mm
Overall width	3.050 – 3.240 mm
Overall height	3.220 mm
Support arms parts	3
Driving power	2 x 2,2 KW
Lifting/Lowering time	ca. 42 s
Software Plattform	ATH HeartBeat
Power supply voltage	3x 400V / C16A
Concrete strength	min. C20/25 4.000 x 2.000 x 180 mm

