

# ATH Matrix Lift® 2.65

## Product Images

---



## Description

---

Electro-hydraulic 2-post lift with quick lift unit and load-dependent lowering function

Synchro Control: Special hydro synchronous control for stepless synchronization without equalization ropes

Safety Control: Electronically monitored synchronization and electromagnetic safety catches

Safety Lock: Load-lowering control onto the safety latches

4-fold roller bearing lift carriage for optimal load transfer

Multifunctional pick-up via double articulated lifting arms and telescopic lifting pads (from e.g. Smart to Sprinter/Crafter long wheel bases)

Without base frame and static connection, variable height adjustment

## Additional Information

---

|                       |                             |
|-----------------------|-----------------------------|
| Rated load capacity   | 6500 kg                     |
| Lifting height max.   | 2165 mm                     |
| Drive-through width   | 2800 mm                     |
| Overall width         | 3920 mm                     |
| Overall height        | 5850 mm                     |
| Support arms parts    | 3 St.                       |
| Driving power         | 3 kW                        |
| Lifting/Lowering time | 50   50 s                   |
| Power supply voltage  | 3x 400V / C16A              |
| Concrete strength     | C 25/30 6.000 x 4.000 x 250 |
| Color                 | RAL 7016 / RAL 9005         |

