ATH W82 Touch 3D Plus

Product Images



- Automatic distance, rim diameter and rim width (3D function) measurement
- Operation directly via 19" touchscreen or ergonomically arranged front control panel
- Digital and optical position display of the weights via LCD touchscreen monitor and duo laser (LPS)
- Static / dynamic, ALU programs, ALU weight optimization and back spoke placement
- Pneumatic rim clamping with 40 mm shaft diameter ("ATH-Quick-hold"), problem-free attachment of the weights via automatic, electronic parking brake ("ATH-Easy-hold"), Measuring tool, integrated interior wheel lighting and incl. wheel lift
- Wheel protection with automatic start-stop function
- Ideally suited for car wheels, with optional accessories also for light truck wheels

Additional Information

Center hole diameter rim	45 – 130 mm
Measurement tolerance	± l g
Measuring time	7 s
Measuring speed	180 U/min
Rim width	1,5 – 20 "
Rim diameter	12 – 24 "
Max. wheel diameter	900 mm
Wheel weight max.	65 kg
Driving power	0,25 kW
Power supply voltage	230V / C16A
Measuring timeMeasuring speedRim widthRim diameterMax. wheel diameterWheel weight max.Driving power	7 s 180 U/min 1,5 - 20 " 12 - 24 " 900 mm 65 kg 0,25 kW

