

# ATH Cross Lift® 50 UGA

## Product Images

---



## Description

---

- High quality and robust scissor lift with hydraulic drive, almost maintenance-free
- Powerful hydraulic unit with load-dependent lowering valve
- Suitable for floor-level installation and installation on the floor with the optional on ground kit
- With recesses for rotating plates at the front, mechanically lockable oscillating plates at the rear, Wheel-free jack (load capacity: 4 t, lifting height: 450 mm), side rails for the optional axle-free jack, removable cross connections, including metal protection bar and switch for the optional 24V LED lighting
- Emergency lowering system for lowering in the event of a power failure, synchronization monitoring via safety light barrier
- Ideally suited for inspection, wheel alignment, repairs and test stations for headlamp and driver assistance systems

## Additional Information

---

|                       |                                    |
|-----------------------|------------------------------------|
| Color                 | Anthrazitgrau / Schwarz            |
| Rated load capacity   | 5.000 kg                           |
| Lifting height max.   | 2.160 mm                           |
| Total platform length | 5.000 mm                           |
| Total platform width  | 600 mm                             |
| Driving power         | 3,5 kW                             |
| Lifting/Lowering time | ca. 70 s                           |
| Power supply voltage  | 3x 400V / C16A                     |
| Concrete strength     | min. C20/25 5.500 x 3.000 x 200 mm |
| Installation depth    | 295 mm                             |

