

ATH Four Lift 55

Product Images



Description

- High-precision manufacturing by laser cutting and robotic welding
- Robust and less sensitive hydraulic drive, almost maintenance-free
- For passenger cars and vehicles with long wheelbase; platform length 5,50 m, one platform is continuously adjustable
- Can be used universally with flat platforms and rails for an optional rolling jack
- Perfect lift for headlamp beam setting due to the notch system for adjusting the platforms
- Only drive-on and repair, no lifting arms
- 2-piece drive-on ramps hinged, perfect for lowered vehicles
- Lifting and lowering with push button control
- Pneumatic unlocking of notches, slack rope protection, emergency lowering system for lowering in case of power failure, CE stop and signal sound
- Perfect lift for automotive repairs and headlamp beam setting

Additional Information

| | |
|-----------------------|------------------------------------|
| Color | Anthrazitgrau / Schwarz |
| Rated load capacity | 5,5 t |
| Lifting height max. | 1.840 mm |
| Drive-on-height | 196 mm |
| Total platform length | 5.190 mm |
| Total platform width | 490 mm |
| Driving power | 2,2 kW |
| Lifting/Lowering time | ca. 45 s |
| Power supply voltage | 3x 400V / C16A |
| Concrete strength | min. C20/25 7.400 x 3.900 x 200 mm |

